



KONICA MINOLTA

**bizhub** C258i

Colour A3 multifunctional

**bizhub  
i-SERIES IS  
SMARTER  
WORKING**  
RETHINK IT



Giving Shape to Ideas

## CUSTOMER BENEFITS



### Intuitive operability

Operate the bizhub like a smartphone or tablet with fully customised user interface



### Mobile connectivity

Print anytime from anywhere with Konica Minolta's innovative mobile technologies



### Security

Secure network integration, data encryption, hard drive overwrite, and advanced user authentication



### Application ecosystem

Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



### Sustainability

Numerous eco features reduce energy consumption and costs

## 1 ENHANCED FEATURES

### OCR text recognition

LK-105v4

### Barcode fonts

LK-106

### Unicode fonts

LK-107

### OCR A and B fonts

LK-108

### Document converter pack

LK-110v2

### ThinPrint® client

LK-111

### Serverless pull printing

LK-114

### Trusted Platform Module

LK-115v2

### Antivirus

LK-116



## 2 CONNECTIVITY

### Fax board

FK-514

### Wireless LAN

UK-221

### USB I/F kit

EK-608

### USB I/F kit

EK-609

### NFC I/F kit

EK-P10

### Biometric authentication

AU-102

### Card authentication

ID card reader

### Mount kit

MK-735

## 3 OTHERS

### Working table

WT-520

### Offline Stapler

FS-P04

### 10-Key pad

KP-P03

### Security kit

SC-510

### Air cleaning unit

CU-102

## 4 MEDIA INPUT

### 1x Universal tray

PC-116

### 2x Universal tray

PC-216

### Large capacity tray

PC-416

### Copier desk

DK-516x

### Banner tray

BT-C1e

## 5 MEDIA OUTPUT

### Job separator

JS-506

### Inner finisher

FS-542

### Punch kit for FS-542

PK-527

### LEGEND

- Mandatory option
- Option
- This option can only be installed with the respective option above it

## FINISHING FUNCTIONALITIES



Corner stapling



Two-point stapling



Two-hole punching



Four-hole punching



Duplex



Combined mixplex/mixmedia



Sheet insertion



Offset sorting



Banner printing



Corner Stapling (offline)

## DESCRIPTION

### ENHANCED FEATURES

|                                  |  |
|----------------------------------|--|
| LK-105v4 OCR text recognition    | Searchable PDF and PPTX  |
| LK-106 Barcode fonts             | Supports native barcode printing   |
| LK-107 Unicode fonts             | Supports native Unicode printing   |
| LK-108 OCR A and B fonts         | Supports native OCR A and B font printing  |
| LK-110v2 Document converter pack | Generates various file formats incl. DOCX, XLSX and PDF/A                            |
| LK-111 ThinPrint® client         | Print data compression for reduced network impact                                    |
| LK-114 Serverless pull printing  | Secure and Follow Me printing solution requiring no server application               |
| LK-115v2 Trusted Platform Module | Trusted Platform Module for protection of data encryption and decryption             |
| LK-116 Antivirus                 | Bitdefender® antivirus provides real time scanning of all incoming and outgoing data |

### CONNECTIVITY

|                                 |   |
|---------------------------------|---|
| FK-514 Fax board                | Super G3 fax, digital fax functionality         |
| UK-221 Wireless LAN             | Wireless LAN and wireless LAN Access Point Mode |
| EK-608 USB I/F kit              | USB keyboard connection                         |
| EK-609 USB I/F kit              | USB keyboard connection; Bluetooth              |
| EK-P10 NFC I/K kit              | To connect with Android mobile devices          |
| AU-102 Biometric authentication | Finger vein scanner                             |
| ID card reader                  | Various ID card technologies                    |
| MK-735 Mount kit                | Installation kit for ID card reader             |

## TECHNICAL SPECIFICATIONS

### SYSTEM SPECIFICATIONS

|                              |  |
|------------------------------|--|
| System speed A4              | Up to 26/26 ppm (mono/colour)  |
| System speed A3              | Up to 15/15 ppm (mono/colour)  |
| Autoduplex speed A4          | Up to 26/26 ppm (mono/colour)  |
| 1st page out time A4         | 5.2/6.8 sec. (mono/colour)   |
| Warm-up time                 | Approx. 16/16 sec. (mono/colour) <sup>1</sup>  |
| Imaging technology           | Laser  |
| Toner technology             | Simitri® V polymerised toner   |
| Panel size/resolution        | 7" / 800 x 480   |
| System memory                | 6,144 MB (standard/max)  |
| System hard drive            | 128 GB (standard) / 256 GB SSD (optional)  |
| Interface                    | 10/100/1,000-Base-T Ethernet; USB 2.0;<br>Wi-Fi 802.11 b/g/n/ac (optional)   |
| Network protocols            | TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour  |
| Automatic document feeder    | Up to 130 originals; A5-A3; 35-128 g/m <sup>2</sup> ; RADF   |
| Printable paper size         | A6-SRA3; customized paper sizes;<br>banner paper max. 1,200 x 297 mm   |
| Printable paper weight       | 52-300 g/m <sup>2</sup>  |
| Paper input capacity         | 1,150 sheets / 3,650 sheets (standard/max)   |
| Paper tray input (standard)  | 1x 500; A6-A3; custom sizes; 52-256 g/m <sup>2</sup><br>1x 500; A5-SRA3; custom sizes; 52-256 g/m <sup>2</sup>                                 |
| Paper tray input (optional)  | 1x 500 sheets; A5-A3; 52-256 g/m <sup>2</sup><br>2x 500 sheets; A5-A3; 52-256 g/m <sup>2</sup><br>1x 2,500 sheets; A4; 52-256 g/m <sup>2</sup> |
| Manual bypass                | 150 sheets; A6-SRA3; custom sizes; banner; 60-300 g/m <sup>2</sup>   |
| Finishing modes (optional)   | Offset; Group; Sort; Staple (offline); Punch   |
| Automatic duplexing          | A6-SRA3; 52-256 g/m <sup>2</sup>   |
| Output capacity              | Up to 250 sheets / up to 500 sheets (standard/max)   |
| Stapling                     | Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m <sup>2</sup> )   |
| Stapling output capacity     | Max. 50 sets   |
| Duty cycle (monthly)         | Rec. 16,000 pages; Max. <sup>2</sup> 130,000 pages   |
| Toner lifetime               | Black up to 28,000 pages<br>CMY up to 28,000 pages   |
| Imaging unit lifetime        | Black up to 175,000/1,000,000 pages (drum/developer)<br>CMY up to 65,000/1,000,000 pages (drum/developer)                                      |
| Power consumption            | 220-240 V / 50/60 Hz; Less than 1.58 kW  |
| System dimension (W x D x H) | 615 x 688 x 899 mm (without options)   |
| System weight                | Approx. 85.0 kg (without options)  |

### OTHERS

|                          |  |
|--------------------------|--|
| WT-520 Working table     | Authentication device placement                  |
| FS-P04 Offline Stapler   | Offline stapler, 20 sheets stapling              |
| KP-P03 10-Key pad        | For use instead of touchscreen                   |
| SC-510 Security kit      | 256 GB SSD; Secure Boot board                    |
| CU-102 Air cleaning unit | Improving indoor air quality by reduced emission |

### MEDIA INPUT

|                            |  |
|----------------------------|--|
| PC-116 1x Universal tray   | 500 sheets, A5-A3, 52-256 g/m <sup>2</sup>                 |
| PC-216 2x Universal tray   | 2x 500 sheets, A5-A3, 52-256 g/m <sup>2</sup>              |
| PC-416 Large capacity tray | 2,500 sheets, A4, 52-256 g/m <sup>2</sup>                  |
| DK-516x Copier desk        | Provides storage space for print media and other materials |
| BT-C1e Banner tray         | Multipage banner feeding                                   |

### MEDIA OUTPUT

|                             |   |
|-----------------------------|---|
| JS-506 Job separator        | Separation of fax output; etc.            |
| FS-542 Inner finisher       | 50-sheet stapling, 500 sheets max. output |
| PK-527 Punch kit for FS-542 | 2/4 hole punching, autoswitching          |

### PRINTER SPECIFICATIONS

|                           |  |
|---------------------------|--|
| Print resolution          | 1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi  |
| Page description language | PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS   |
| Operating systems         | Windows 10 (32/64); Windows 11; Windows Server 2016;<br>Windows Server 2019; Windows Server 2022;<br>Windows Server 2025;<br>macOS 10.14 or later; Unix; Linux; Citrix |
| Printer fonts             | 80 PCL Latin; 137 PostScript 3 Emulation Latin;<br>Barcode fonts (optional); OCR A and B fonts (optional);<br>Unicode fonts (optional)                                 |
| Mobile printing           | AirPrint (iOS); Mopria (Android);<br>Konica Minolta Mobile Print (iOS/Android)<br>optional: WiFi Direct  |

### SCANNER SPECIFICATIONS

|                   |  |
|-------------------|--|
| Scan speed        | Up to 70/70 ipm in simplex (mono/colour)<br>Up to 24/24 ipm in duplex (mono/colour)  |
| Scan resolution   | Up to 600 x 600 dpi  |
| Scan modes        | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);<br>Scan-to-FTP; Scan-to-SFTP; Scan-to-Box; Scan-to-USB;<br>Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan |
| File formats      | JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS;<br>PPTX; PDF/A 1a and 1b<br>optional: Searchable PDF; Searchable DOCX/PPTX/XLSX                           |
| Scan destinations | 2,000 destinations + 100 groups; LDAP support  |

### COPIER SPECIFICATIONS

|                 |                                     |
|-----------------|-------------------------------------|
| Copy resolution | 600 x 600 dpi                       |
| Gradation       | 256 gradations                      |
| Multicopy       | 1-9,999                             |
| Original format | Max. A3                             |
| Magnification   | 25-400% in 0.1% steps; Auto-zooming |

## FAX SPECIFICATION

|                  |                                       |
|------------------|---------------------------------------|
| Fax standard     | Super G3 (optional)                   |
| Fax transmission | Analogue; i-Fax; Colour i-Fax; IP-Fax |
| Fax resolution   | Up to 600 x 600 dpi                   |
| Fax compression  | MH; MR; MMR; JBIG                     |
| Fax modem        | Up to 33.6 Kbps                       |
| Fax destinations | 2,000 single + 100 groups             |

## USER BOX SPECIFICATIONS

|                      |  |
|----------------------|--|
| Storable documents   | Up to 3,000 documents or 3,000 pages   |
| Type of user boxes   | Public; Personal (with password or authentication);<br>Group (with authentication) |
| Type of system boxes | Secure print; Encrypted PDF print; Fax receipt; Fax polling                        |

## SYSTEM FEATURES

|            |   |
|------------|---|
| Security   | ISO 15408 HCD-cPP Common Criteria (in evaluation);<br>IP filtering and port blocking;<br>TLS1.2/1.3 secure network communication; IPsec support;<br>IEEE 802.1x support; User authentication; Authentication log;<br>Secure print; Kerberos; Hard drive overwrite;<br>Hard drive data encryption (AES 256); Confidential fax;<br>Print user data encryption<br>optional: Antivirus realtime scanning (Bitdefender®) |
| Accounting | Up to 1,000 user accounts; Active Directory support (user name +<br>password + e-mail + smb folder); User function access definition;<br>optional: Biometric authentication (finger vein scanner);<br>ID card authentication (ID card reader);<br>Authentication by mobile device (Android/iOS)   |
| Software   | Data Administrator; Web Connection; Driver Packaging Utility;<br>Log Management Utility; Font Management Utility;<br>Download Manager   |

<sup>1</sup> Warm-up time may vary depending on the operating environment and configuration

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

