

bizhub 225i

Black & White A3 multifunctional





CUSTOMER BENEFITS




ServicesEfficient printer fleet management, including automatic con-sumables delivery, pro-active maintenance and remote setup


OPTIONS













FINISHING FUNCTIONALITIES





Duplex

Stapling (offline)

DESCRIPTION

CONNECTIVITY

| FK-510 Fax board | Super G3 fax |
|--------------------------|---|
| SX-BR-300AN Wireless LAN | Wireless LAN to network connector |
| MK-750 Optional Panel | Needed for fax function and scan one-touch destinations |

OTHERS

| * · · · = · · · | |
|------------------------|---|
| DF-633 Document feeder | Reversing automatic document feeder, capacity 130 originals |
| OC-512 Original Cover | Cover instead of ADF |
| AD-509 Duplex unit | For duplex printing and copying |

MEDIA INPUT

| PF-507 Paper Tray | 250 sheets, B5-A3, 64-90 g/m ² |
|-----------------------------|---|
| DK-706 Copier desk (large) | For no or 1x PF-507 |
| DK-707 Copier desk (medium) | For 2x PF-507 |
| DK-708 Copier desk (small) | For 3x or 4x PF-507 |

MEDIA OUTPUT

| EH-C591 Convenience stapler | Convenient stapling of up to 50 sheets per set |
|-----------------------------|--|
|-----------------------------|--|

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

| System speed A4 | Up to 22 ppm |
|--------------------------------------|--|
| System speed A3 | Up to 8 ppm |
| Autoduplex speed A4 | Up to 15 ppm |
| 1st page out time A4 | 6.5 sec. |
| Warm-up time | Approx. 15 sec. ¹ |
| Imaging technology | Laser |
| Toner technology | Simitri® HD polymerised toner |
| Panel size/resolution | 5 line LCD / 128 x 64 |
| System memory | 256 MB (standard/max) |
| Interface | 10/100-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n (optional) |
| Network protocols | TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP |
| Automatic document feeder (optional) | Up to 130 originals; A5–A3; 35–128 g/m²; RADF |
| Printable paper size | A5–A3; customized paper sizes |
| Printable paper weight | 64-157 g/m ² |
| Paper input capacity | 350 sheets/1,350 sheets (standard/max) |
| Paper tray input (standard) | $1x 250$; A5-A3; custom sizes; 64–157 g/m^2 |
| Paper tray input (optional) | 1x 250 sheets; B5-A3; custom sizes; 64–90 g/m² (up to $4x$) |
| Manual bypass | 100 sheets; A5-A3; custom sizes; $64-157 \text{ g/m}^2$ |
| Finishing modes (optional) | Group; Sort; Staple (offline) |
| Automatic duplexing | A5-A3; 64-90 g/m ² |
| Output capacity | Up to 250 sheets |
| Duty cycle (monthly) | Rec. 5,000 pages; Max. ² 15,000 pages |
| Toner lifetime | Black up to 12,000 pages |
| Imaging unit lifetime | Black up to 55,000/55,000 pages (drum/developer) |
| Power consumption | 220-240 V / 50/60 Hz; Less than 1.30 kW |
| System dimension (W x D x H) | 607 x 570 x 458 mm (without options) |
| System weight | Approx. 28.2 kg (without options) |

PRINTER SPECIFICATIONS

| Print resolution | 600 x 600 dpi |
|---------------------------|---|
| Page description language | GDI |
| Operating systems | Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); |
| | Windows Server 2008 (32/64); Windows Server 2008 R2; |
| | Windows Server 2012; Windows Server 2012 R2; Windows Server |
| | 2016; Windows Server 2019; Linux |

SCANNER SPECIFICATIONS

| Up to 55/20 ipm in simplex (mono/colour) |
|---|
| Up to 600 x 600 dpi |
| Scan-to-eMail; Scan-to-SMB; Scan-to-FTP; Scan-to-USB; |
| TWAIN scan |
| JPEG; TIFF; PDF |
| 32 destinations; 250 speed dials; LDAP support |
| |

COPIER SPECIFICATIONS

| Copy resolution | 600 x 600 dpi |
|-----------------|-------------------------------------|
| Gradation | 256 gradations |
| Multicopy | 1–999 |
| Original format | Max. A3 |
| Magnification | 25–400% in 0.1% steps: Auto-zooming |

FAX SPECIFICATIONS

| Fax standard | Super G3 (optional) |
|------------------|----------------------------------|
| Fax transmission | Analogue; i-Fax |
| Fax resolution | Up to 406 x 392 dpi |
| Fax compression | MH; MR; MMR; JBIG |
| Fax modem | Up to 33.6 Kbps |
| Fax destinations | 32 destinations; 250 speed dials |
| | |

SYSTEM FEATURES

| 3131EMITEATORES | |
|-----------------|---|
| Accounting | Up to 50 user accounts |
| Software | Net Care Device Manager; Web Connection |

¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m² quality.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
 particular page size (6% coverage of A4). The actual life of each consumable will vary depending on use and other printing $variables\ including\ page\ coverage,\ page\ size,\ media\ type,\ continuous\ or\ intermittent\ printing,\ ambient\ temperature\ and$ humidity.
- Some of the product illustrations contain optional accessories.
 Specifications and accessories are based on the information available at the time of printing and are subject to change
- without notice.

 Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.











